

ST. NICHOLAS STOLE

FABRIC REQUIRED

1 3/8 yards, 45-inch fabric, *adjust, if needed, for repeat*

1 3/4 yards interfacing, *light or medium weight*

Gold trim, *as desired*

PATTERN PIECES

Stole, piece #6, cut 2 or 4 if self-facing

Stole Lining, piece #6, cut 2 if using lining fabric

Stole Interfacing, piece #6, cut 2

Seam allowances 5/8" – 3/4"

Secure all seams at beginning and end

STOLE SEWING INSTRUCTIONS

1. Decide placement for gold trim. Stitch in place by hand or machine.
The model has gold trim placed 5-1/2 to 5-3/4-inches from bottom edge, including seam allowance.
2. Place interfacing on the **WRONG SIDE** of the stole pieces (#6).
Pin stole piece to lining piece (either same or lining fabric) **RIGHT SIDES TOGETHER**.
Stitch leaving top (center back seam) open. *This is the two long sides and across the bottom.*
Repeat for second stole piece..
3. Trim, layering seam and clip corners.
Turn each half right side out and press.
4. With front **RIGHT SIDES** of stole together stitch the top side from one side seam to the other.
5. Turn stole so the inside back is up.
Fold lining seam allowance under so each side meets like a seam.
Overcast the edges together where they meet.
Press.

